

# YY-07HD

## Heavy-Duty Horizontal Foam Cutting Machine

### 强力型海绵平切机

技术规格	TECHNICAL SPECIFICATION
机身尺寸: 6m × 5m × 2.5m(L × W × H)	Floor Size Required : L7m×W7m×H3m
平台尺寸: 3.2m × 2.4m(L × W)	Machine Dimension: L 6m×W 5m×H 2.5m
可裁切海棉尺寸: 3m × 2.2m × 1.2m(L × W × H)	Foam Cutting Thickness : 3-25mm
可裁切海棉厚度: 3 mm~25mm	Working Width : 2200mm
裁切速度: 5-30 m/min	Working Length : 3000mm
平台移动马达: 3HP附减速机和变频器	Cutting And Stacking Height : 1200mm
刀带马达: 3HP-6P	Working Table Size : 3200mm×2200mm
升降螺杆: 使用滚珠式德国进口螺杆	2 Sharpener Motors
上升下降马达: 2HP附减速机	Cutting Tolerance ± 0.25mm
磨刀马达: 1/8HP × 2	Automatic Roller Adjustment For Height
电控制操作箱: 日本三菱PLC	Pneumatic Blade Tightener



#### Feature:

- Stationary cutting unit
- Circulating bandknife being sharpened by a motorized grinding device during the cutting procedure
- Bandknife width 50 mm; service life about 100-150 hours
- 3-digit number of automatic programmes that can be saved with pre-selection of number of number of pieces, layer thickness [ 3-25mm with increments of 0.5mm]
- Cutting angle and table speed separately adjustable for forward and backward movement
- Cutting speed infinitely adjustable [5-30m/min]
- Table material : wood plate covered with sandpaper

#### Advantages:

- Excellent efficiency, particularly with larger amounts of sheets for rebounding foams or flexible high density material foams to be split horizontally
- Working Table with vacuum system which is able to hold foam material
- Stable operation table

**主要用途:** 本机主要用于再生泡绵以及高密度海绵的切片工作